

KEL-DPZ-E

Cable entry plates





Conical shape on back provides additional sealing and strain relief



Also available in black.



Description	Type	Order No.	Number of cables	PU
	KEL-DPZ-E 112 7	<div> <div>43780</div> <div>50780</div> </div>	7 × 7.5 - 12 mm	10
	KEL-DPZ-E 112 21	<div> <div>43790</div> <div>50790</div> </div>	21 × 3.2 - 6.5 mm	10

* Only valid for grey product types

Product description

KEL-DPZ-E is designed for routing cables without connectors without connectors in very small space.

2.1

The assembly of the KEL-DPZ-E with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane, push the cables through. The KEL-DPZ-E provides strain relief and protection IP66 / UL type 12.

With an area of only 18 × 112 mm, up to 21 cables can be easily routed and sealed.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

Advantages & benefits

- Space saving shape
 - Dual sealing of cables acc. to IP66/UL type 12
 - High cable density
 - Fast and easy assembly
 - Hygienic design

Specifications

Material	Frame: Polyamide (PA)
Colour	Sealing plate: Elastomer
	<div> <div>grey (similar RAL 7035)</div> <div>black</div> </div>
Flame class	UL94-Vo, self-extinguishing
IP rating	IP66 (certified acc. to EN 60529)
UL type rating	UL type 12 (acc. to UL 50E)
Temperature	- 40°C to + 100°C (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	18 × 112 mm / page 220 - 221
Plate depth	14 mm

Accessories

ST-B Plugs	93
KEL-EMC-PF Cable collectors	149