

KEL-QUICK

Cable entry frames for quick assembly



Configure online now

IP54



Cover lid is simply snapped onto the frame.



Tool-free mounting with KEL-SNAP frame.



Slit QT grommets

Product description

The KEL-QUICK range is a compact system to route and seal pre-terminated cables as well as conduits or pneumatic hoses utilising split QT grommets. After populating the entry frame with QT grommets and cables, the cover lid is snapped onto the frame without using tools. The KEL-QUICK frames match exactly the cut-out dimensions for 24-, 16- and 10-pin standard industrial connectors. The KEL-QUICK-B matches cut-out dimensions of 36x46 mm. KEL-QUICK frames can either be screw mounted or simply snapped into the KEL-SNAP frame. A flat rubber gasket is included in the shipment.

Advantages & benefits





- Fast and easy assembly and when used with the KEL-SNAP frame, mounting without tools possible
- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density, wide variety of grommets

Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
IP rating	IP54, with gasket and correct selection of the cable grommets
Temperature Properties	- 40°C to + 140°C (static)
Drilling template	See Page 218 - 219
Frame depth	17 mm

Accessories

QT Cable grommets	66
KEL-SNAP Mounting frames	31
KEL-EMC Cable collectors	148 - 150
KDR Base plates	174 - 187
FP Flange plates	194 - 203
MP Module plates	188 - 189
ST Plugs	53

Description	Type	Order No.	Cut-out [mm]	Grommets	PU	
		KEL-QUICK 24 10	42410	36 × 112	10 –	10
	NEW	KEL-QUICK 24 7	42412	36 × 112	6 1	10
	NEW	KEL-QUICK 24 4	42413	36 × 112	2 2	10
		KEL-QUICK 16 8	42418	36 × 86	8 –	10
	NEW	KEL-QUICK 16 5	42425	36 × 86	4 1	10
	NEW	KEL-QUICK 16 2	42426	36 × 86	0 2	10
		KEL-QUICK 10 6	42420	36 × 65	6 –	10
	NEW	KEL-QUICK 10 3	42427	36 × 65	2 1	10
		KEL-QUICK-B4	42434	36 × 46	4 –	10

KEL-QUICK-E

Cable entry frames for quick assembly

Configure online now



Cover lid is simply snapped onto the frame.







Slit QT grommets



IP54

1.21

Description	Type	Order No.	Cut-out [mm]	Grommets	PU
	KEL-QUICK-E5	42424	24 × 112	5 QT	10
	KEL-QUICK-E4	42423	24 × 86	4 QT	10
	KEL-QUICK-E3	42422	24 × 65	3 QT	10
	KEL-QUICK-E2	42421	24 × 43	2 QT	10

Product description

The KEL-QUICK-E range is a compact single row system to route and seal pre-terminated cables as well as conduits or pneumatic hoses utilising split QT grommets. The KEL-QUICK-E version is particularly suited for flat connectors. The small frame is ideal for applications with limited space.

After populating the entry frame with QT grommets and cables, the cover lid is snapped onto the frame without using tools. A flat rubber gasket is included in the shipment.

Advantages & benefits

- Fast and easy assembly by locking the frame without tools
- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density, wide variety of grommets

Specifications

Material	Polyamide (PA)
Flame class	UL94-Vo, self-extinguishing
IP rating	IP54, with gasket and correct selection of the cable grommets
Temperature Properties	- 40°C to + 140°C (static)
Drilling template	See Page 220 - 221
Frame depth	17 mm

Accessories

QT Cable grommets	66
KEL-EMC Cable collectors	148 - 150
ST Plugs	53