


KEL-DPZ-CLICK multi-membrane cable entry plates

for snap-in mounting, M25 - M63 / IP65 / IP66 / IP68



[Request your free sample »](#)

KEL-DPZ-CLICK cable entry plates are designed to route and seal cables without connectors or fibre optics (from 1.5 mm to 22 mm in diameter) in limited space.

The new variant of the proven cable entry plate KEL-DPZ is snapped into the cut-out directly from the front. This significantly reduces the assembly time. Alternatively, the new variant can be fastened with a locknut. The KEL-DPZ-CLICK series have a thread to fit in metric cut-outs from M25 to M63. Thus cut-outs for metric cable glands can be used.

Snapped into the cut-out:

For wall thickness 1 – 2.5 mm
Protection IP65

Fixed with a locknut:

For max. wall thickness 11 mm
Protection IP66 / IP68

The assembly of the KEL-DPZ-CLICK with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane, push the cables through. The KEL-DPZ-CLICK provides strain relief and protection IP65 / IP66 / IP68.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.



Specifications

IP rating (certified acc. to EN 60529)	IP54, IP55, IP64, IP65, IP66, IP67, IP68
Material	Elastomer Base frame: Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 100 C°
Properties	silicone free, halogen free
Mounting options	Fasten with locknut, Snap-in

Advantages & benefits

- Fast mounting
- Offers two mounting types: Snap-in and locknut fixation
- High cable density
- Certified protection classes IP65/IP66/IP68 (acc. to EN 60529)
- Automatic sealing and strain relief for the cable
- Suitable for metric cut-outs
- Hygienic design - free of dirt-collecting recesses

Product types & sizes

KEL-DPZ-CLICK 25|3 gy




Part No.	44050	Mounting height	8 mm
EAN	4251269323065	Cut-out size, round	25.3 mm
PU	10	Cut-out size, metric	M25
For max. no. of cables	3	Thread	M25 x 1,5
Colour	grau (ähnlich RAL 7035)	Thread length	20 mm
Height	28 mm	Clamping range	2 x 3.2 - 5.2 mm
External diameter	39 mm		1 x 3.2 - 6.5 mm

KEL-DPZ-CLICK 25|3 bk


Part No. **50050**
 EAN **4251269323218**
 PU **10**
 For max. no. of cables **3**
 Colour **schwarz**
 Height **28 mm**
 External diameter **39 mm**

Mounting height **8 mm**
 Cut-out size, round **25.3 mm**
 Cut-out size, metric **M25**
 Thread **M25 x 1,5**
 Thread length **20 mm**
 Clamping range **2 x 3.2 - 5.2 mm**
1 x 3.2 - 6.5 mm

KEL-DPZ-CLICK 25|4 gy


Part No. **44051**
 EAN **4251269323072**
 PU **10**
 For max. no. of cables **4**
 Colour **grau (ähnlich RAL 7035)**
 Height **28 mm**
 External diameter **39 mm**

Mounting height **8 mm**
 Cut-out size, round **25.3 mm**
 Cut-out size, metric **M25**
 Thread **M25 x 1,5**
 Thread length **20 mm**
 Clamping range **4 x 3.2 - 5.2 mm**

KEL-DPZ-CLICK 25|4 bk

Part No. **50051**
 EAN **4251269323225**
 PU **10**
 For max. no. of cables **4**
 Colour **schwarz**
 Height **28 mm**
 External diameter **39 mm**

Mounting height **8 mm**
 Cut-out size, round **25.3 mm**
 Cut-out size, metric **M25**
 Thread **M25 x 1,5**
 Thread length **20 mm**
 Clamping range **4 x 3.2 - 5.2 mm**

KEL-DPZ-CLICK 32|4 gy


Part No. **44052**
 EAN **4251269323089**
 PU **10**
 For max. no. of cables **4**
 Colour **grau (ähnlich RAL 7035)**
 Height **28 mm**
 External diameter **44 mm**

Mounting height **8 mm**
 Cut-out size, round **32.3 mm**
 Cut-out size, metric **M32**
 Thread **M32 x 1,5**
 Thread length **20 mm**
 Clamping range **3 x 3.2 - 6.5 mm**
1 x 7.2 - 12.5 mm

KEL-DPZ-CLICK 32|4 bk

Part No. **50052**
 EAN **4251269323232**
 PU **10**
 For max. no. of cables **4**
 Colour **schwarz**
 Height **28 mm**
 External diameter **44 mm**

Mounting height **8 mm**
 Cut-out size, round **32.3 mm**
 Cut-out size, metric **M32**
 Thread **M32 x 1,5**
 Thread length **20 mm**
 Clamping range **3 x 3.2 - 6.5 mm**
1 x 7.2 - 12.5 mm

KEL-DPZ-CLICK 32|4-2 gy


Part No. **44053**
 EAN **4251269323096**
 PU **10**
 For max. no. of cables **4**
 Colour **grau (ähnlich RAL 7035)**
 Height **28 mm**
 External diameter **44 mm**

Mounting height **8 mm**
 Cut-out size, round **32.3 mm**
 Cut-out size, metric **M32**
 Thread **M32 x 1,5**
 Thread length **20 mm**
 Clamping range **4 x 5 - 9.5 mm**

**KEL-DPZ-CLICK 32|4-2
bk**

Part No. **50053**
 EAN **4251269323249**
 PU **10**
 For max. no. of cables **4**
 Colour **schwarz**
 Height **28 mm**
 External diameter **44 mm**

Mounting height **8 mm**
 Cut-out size, round **32.3 mm**
 Cut-out size, metric **M32**
 Thread **M32 x 1,5**
 Thread length **20 mm**
 Clamping range **4 x 5 - 9.5 mm**

KEL-DPZ-CLICK 32|7 gy


Part No. **44054**
 EAN **4251269323102**
 PU **10**
 For max. no. of cables **7**
 Colour **grau (ähnlich RAL 7035)**
 Height **28 mm**
 External diameter **44 mm**

Mounting height **8 mm**
 Cut-out size, round **32.3 mm**
 Cut-out size, metric **M32**
 Thread **M32 x 1,5**
 Thread length **20 mm**
 Clamping range **7 x 3.2 - 6.5 mm**

KEL-DPZ-CLICK 32|7 bk

Part No. **50054**
 EAN **4251269323256**
 PU **10**
 For max. no. of cables **7**
 Colour **schwarz**
 Height **28 mm**
 External diameter **44 mm**

Mounting height **8 mm**
 Cut-out size, round **32.3 mm**
 Cut-out size, metric **M32**
 Thread **M32 x 1,5**
 Thread length **20 mm**
 Clamping range **7 x 3.2 - 6.5 mm**

KEL-DPZ-CLICK 40|8 gy

Part No. **44055**
 EAN **4251269323119**
 PU **10**
 For max. no. of cables **8**
 Colour **grau (ähnlich RAL 7035)**
 Height **28 mm**
 External diameter **52 mm**

Mounting height **8 mm**
 Cut-out size, round **40.4 mm**
 Cut-out size, metric **M40**
 Thread **M40 x 1,5**
 Thread length **20 mm**
 Clamping range **4 x 3.2 - 6.5 mm**
4 x 5 - 10.2 mm

KEL-DPZ-CLICK 40|8 bk

Part No. **50055**
 EAN **4251269323263**
 PU **10**
 For max. no. of cables **8**
 Colour **schwarz**
 Height **28 mm**
 External diameter **52 mm**

Mounting height **8 mm**
 Cut-out size, round **40.4 mm**
 Cut-out size, metric **M40**
 Thread **M40 x 1,5**
 Thread length **20 mm**
 Clamping range **4 x 3.2 - 6.5 mm**
4 x 5 - 10.2 mm

KEL-DPZ-CLICK 50|8 gy

Part No. **44056**
 EAN **4251269323126**
 PU **10**
 For max. no. of cables **8**
 Colour **grau (ähnlich RAL 7035)**
 Height **28 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50.4 mm**
 Cut-out size, metric **M50**
 Thread **M50 x 1,5**
 Thread length **20 mm**
 Clamping range **5 x 5 - 10.2 mm**
3 x 7.2 - 12.5 mm

KEL-DPZ-CLICK 50|8 bk

Part No. **50056**
 EAN **4251269323270**
 PU **10**
 For max. no. of cables **8**
 Colour **schwarz**
 Height **28 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50.4 mm**
 Cut-out size, metric **M50**
 Thread **M50 x 1,5**
 Thread length **20 mm**
 Clamping range **5 x 5 - 10.2 mm**
3 x 7.2 - 12.5 mm

KEL-DPZ-CLICK 50|10 gy


Part No. **44057**
 EAN **4251269323133**
 PU **10**
 For max. no. of cables **10**
 Colour **grau (ähnlich RAL 7035)**
 Height **28 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50.4 mm**
 Cut-out size, metric **M50**
 Thread **M50 x 1,5**
 Thread length **20 mm**
 Clamping range **7 x 3.2 - 6.5 mm**
2 x 5 - 10.2 mm
1 x 16 - 22.2 mm

KEL-DPZ-CLICK 50|10 bk

Part No. **50057**
 EAN **4251269323287**
 PU **10**
 For max. no. of cables **10**
 Colour **schwarz**
 Height **28 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50.4 mm**
 Cut-out size, metric **M50**
 Thread **M50 x 1,5**
 Thread length **20 mm**
 Clamping range **7 x 3.2 - 6.5 mm**
2 x 5 - 10.2 mm
1 x 16 - 22.2 mm

KEL-DPZ-CLICK 50|12 gy


Part No. **44058**
 EAN **4251269323140**
 PU **10**
 For max. no. of cables **12**
 Colour **grau (ähnlich RAL 7035)**
 Height **28 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50.4 mm**
 Cut-out size, metric **M50**
 Thread **M50 x 1,5**
 Thread length **20 mm**
 Clamping range **4 x 3.2 - 6.5 mm**
8 x 5 - 10.2 mm

KEL-DPZ-CLICK 50|12 bk


Part No. **50058**
 EAN **4251269323294**
 PU **10**
 For max. no. of cables **12**
 Colour **schwarz**
 Height **28 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50.4 mm**
 Cut-out size, metric **M50**
 Thread **M50 x 1,5**
 Thread length **20 mm**
 Clamping range **4 x 3.2 - 6.5 mm**

KEL-DPZ-CLICK 50|19 gy


Part No. **44059**
 EAN **4251269323157**
 PU **10**
 For max. no. of cables **19**
 Colour **grau (ähnlich RAL 7035)**
 Height **28 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50.4 mm**
 Cut-out size, metric **M50**
 Thread **M50 x 1,5**
 Thread length **20 mm**
 Clamping range **19 x 3.2 - 6.5 mm**

**KEL-DPZ-CLICK 50|19
bk**

Part No. **50059**
 EAN **4251269323300**
 PU **10**
 For max. no. of cables **19**
 Colour **schwarz**
 Height **28 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50.4 mm**
 Cut-out size, metric **M50**
 Thread **M50 × 1,5**
 Thread length **20 mm**
 Clamping range **19 x 3.2 - 6.5 mm**

**KEL-DPZ-CLICK 50|78
gy**

Part No. **44060**
 EAN **4251269323164**
 PU **10**
 For max. no. of cables **78**
 Colour **grau (ähnlich RAL 7035)**
 Height **28 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50.4 mm**
 Cut-out size, metric **M50**
 Thread **M50 × 1,5**
 Thread length **20 mm**
 Clamping range **76 x 1.5 - 2.6 mm**
2 x 2.5 - 5 mm

**KEL-DPZ-CLICK 50|78
bk**

Part No. **50060**
 EAN **4251269323317**
 PU **10**
 For max. no. of cables **78**
 Colour **schwarz**
 Height **28 mm**
 External diameter **62 mm**

Mounting height **8 mm**
 Cut-out size, round **50.4 mm**
 Cut-out size, metric **M50**
 Thread **M50 × 1,5**
 Thread length **20 mm**
 Clamping range **76 x 1.5 - 2.6 mm**
2 x 2.5 - 5 mm

KEL-DPZ-CLICK 63|9 gy

Part No. **44061**
 EAN **4251269323171**
 PU **10**
 For max. no. of cables **9**
 Colour **grau (ähnlich RAL 7035)**
 Height **28 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63.4 mm**
 Cut-out size, metric **M63**
 Thread **M63 × 1,5**
 Thread length **20 mm**
 Clamping range **1 x 3.2 - 6.5 mm**
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm

KEL-DPZ-CLICK 63|9 bk

Part No. **50061**
 EAN **4251269323324**
 PU **10**
 For max. no. of cables **9**
 Colour **schwarz**
 Height **28 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63.4 mm**
 Cut-out size, metric **M63**
 Thread **M63 × 1,5**
 Thread length **20 mm**
 Clamping range **1 x 3.2 - 6.5 mm**
3 x 5 - 10.2 mm
4 x 9 - 16.2 mm
1 x 16 - 22.2 mm

**KEL-DPZ-CLICK 63|13
gy**

Part No. **44062**
 EAN **4251269323188**
 PU **10**
 For max. no. of cables **13**
 Colour **grau (ähnlich RAL 7035)**
 Height **28 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63.4 mm**
 Cut-out size, metric **M63**
 Thread **M63 × 1,5**
 Thread length **20 mm**
 Clamping range **4 x 3.2 - 6.5 mm**
4 x 5 - 10.2 mm
5 x 9 - 16.2 mm

**KEL-DPZ-CLICK 63|13
bk**

Part No. **50062**
 EAN **4251269323331**
 PU **10**
 For max. no. of cables **13**
 Colour **schwarz**
 Height **28 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63.4 mm**
 Cut-out size, metric **M63**
 Thread **M63 x 1,5**
 Thread length **20 mm**
 Clamping range **4 x 3.2 - 6.5 mm**
4 x 5 - 10.2 mm
5 x 9 - 16.2 mm

**KEL-DPZ-CLICK 63|14
gy**


Part No. **44063**
 EAN **4251269323195**
 PU **10**
 For max. no. of cables **14**
 Colour **grau (ähnlich RAL 7035)**
 Height **28 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63.4 mm**
 Cut-out size, metric **M63**
 Thread **M63 x 1,5**
 Thread length **20 mm**
 Clamping range **14 x 5 - 10.2 mm**

**KEL-DPZ-CLICK 63|14
bk**


Part No. **50063**
 EAN **4251269323348**
 PU **10**
 For max. no. of cables **14**
 Colour **schwarz**
 Height **28 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63.4 mm**
 Cut-out size, metric **M63**
 Thread **M63 x 1,5**
 Thread length **20 mm**
 Clamping range **14 x 5 - 10.2 mm**

**KEL-DPZ-CLICK 63|35
gy**

Part No. **44064**
 EAN **4251269323201**
 PU **10**
 For max. no. of cables **35**
 Colour **grau (ähnlich RAL 7035)**
 Height **28 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63.4 mm**
 Cut-out size, metric **M63**
 Thread **M63 x 1,5**
 Thread length **20 mm**
 Clamping range **35 x 3.2 - 6.5 mm**

**KEL-DPZ-CLICK 63|35
bk**

Part No. **50064**
 EAN **4251269323355**
 PU **10**
 For max. no. of cables **35**
 Colour **schwarz**
 Height **28 mm**
 External diameter **75 mm**

Mounting height **8 mm**
 Cut-out size, round **63.4 mm**
 Cut-out size, metric **M63**
 Thread **M63 x 1,5**
 Thread length **20 mm**
 Clamping range **35 x 3.2 - 6.5 mm**